



Demand more. Choose Foster


## DRP22T Freezer Retarder Prover Cabinet

# DRP22T



### Temperature


---

 Dough Retarder Prover -10/40 °C

### Dimensions (mm)

---

W 816 D 1101  
H 2230



### Capacity

---

250 KG 24hr

### Unpacked Weight

---

181 KG

### Features & Benefits

---

The Foster Bakery Range helps you plan and prepare your production to overcome the peaks and troughs associated with every bakery, ensuring you make the very best use of your time and available storage space.

- State of the art design - giving the reliability, energy efficiency and performance you expect from Foster
- Variable retarding temperature options between  $-4\frac{2}{1}$  and  $+4\frac{2}{1}$  C
- Automatic humidity control prevents skinning and weight loss
- Sophisticated airflow system ensures even temperature and humidity throughout
- High Quality 304 Stainless Steel Exterior Build Quality

External Finish	
304 Stainless Steel	Standard
Internal Finish	
304 Stainless Steel	Option
Aluminium	Standard
Shelving	
Bakery Capacity: 20 Tray - 30x18	Standard
Bakery Capacity: 20 Tray - 60x40	Option
Base Fittings	
80mm Castors	Standard

Doors	
Hinged - Right Hand	Standard
Hinged - Left Hand	Option
Refrigeration	
Forced Air	Standard
Integral	Standard
R404a	Standard

Electrical Data & Service Information	
230 Volts	Standard
50Hz	Standard
1 Phase	Standard
Running Watts	1870
Running Amps	5.5
Thermal Heat Rejection (W)	1,950
Noise (dBa @ 1m)	TBC
Fuse Required (A)	13 amp

## Footnotes

- Bakers trays not supplied as standard
- All the above models are built to take 30" x 18" trays as standard. If it is required to take 60 x 80 cm trays, please specify this at the time of ordering by adding a 'C' prefix eg. C PRO 20 DR
- Extra pairs of stainless steel trayslides available
- Electrical supply 230/1/50
- Water inlet connection size 3/4" BSP and drain outlet required

**FOR MORE INFORMATION CONTACT  
TRIDENT REFRIGERATION ON  
01895 637900**

**FOSTER  
GREEN  
PROCUREMENT**



**Demand more. Choose Foster**