



Demand more. Choose Foster

Eco Pro G2 1/3 Refrigerated Counter EP13H



Temperature



Refrigerator 1/4 °C

Dimensions (mm)

W 1865 D 700

H 865



Capacity

435 Litres

Unpacked Weight

145 KG

Features & Benefits

Providing excellence and practicality at a very competitive price, the Eco Pro range generates significant energy and carbon reductions in use saving you money on your operating costs whilst at the same time never compromising on your commitment to food safety

- High Quality 304 Stainless Steel Exterior Build Quality
- 60mm all-round insulation improves energy efficiency
- Fully floating lock provides durable security and prevents lock breakage if the key is left in
- Energy-saving Hydrocarbon refrigerant option at no extra cost
- Concealed refrigeration system maximises capacity with a tidy and practical interior

External Finish	
304 Stainless Steel	Standard
304 Stainless Steel Rear For Island Siting	Option

Internal Finish	
304 Stainless Steel	Option
Aluminium	Standard

Shelving	
Additional Shelf	Option
Nylon Coated Gastronorm 1/1 Shelf	Quantity: 6 Standard

Base Fittings	
80mm Castors	Standard
150mm Legs	Option
Levelling Bolts	Option

Doors	
Solid Full	Standard
Glass with Lights	Option

Worktop & Drawers	
<h2>Temperature</h2>	
Worktop	Standard
100mm Splashback	Option
Saladette Cut Out	Option
Night Cover for Saladette Cutout	Option
Less Worktop	Option
1/2 Drawers	Option
1/3 Drawers	Option

Refrigeration	
Forced Air	Standard
Integral	Standard
Remote - less condensing unit	Option
R290 (Hydrocarbon)	Option
R134a	Standard
Drain Required?	No

Electrical Data & Service Information	
230 Volts	Standard
50Hz	Standard
1 Phase	Standard
Running Watts	260
Running Amps	1.8
Thermal Heat Rejection (W)	270
Noise (dBa @ 1m)	67.2
Fuse Required (A)	10 amp

Product Extras	
Helicoil Mains Lead	Option
Marine Kit	Option
Width Reduction (178mm reduction available when remote option selected)	Option

Footnotes

- Where glass door option is requested please note that every door supplied is glass.
- Hydrocarbon option not available on glass door models
- Glass doors not available on 60Hz option
- 32oC ambient on glass door refrigerator model
- Any mix of two or three drawer units is possible, as is any combination of drawers and doors. Important - drawer sections are supplied without shelves. Will accommodate pans (optional extra): 1/2 drawers up to 150mm, 1/3 drawers up to 100mm (top drawer max. 70mm on 1/3 drawers).
- Marine kit option includes legs, bulkhead brackets, rat proofing & marine shelves.
- Castors not available if product supplied less condensing unit
- 100mm leg option: height ranges from 835 to 865mm (replacement for standard castors). 150mm legs: height ranges from 885 to 935mm.
- Depth with door open is 1113mm
- Decibel rating measured 1m high from the floor and 1m out from the cabinet.
- 60Hz model supplied as 220v machine with separate transformer for conversion to 115v supply.
- Adequate airflow must be kept around the counter: 150mm

FOSTER
GREEN
PROCUREMENT



CORPORATE SOCIAL
RESPONSIBILITY



INDEPENDENT
VERIFICATION



HYDROCARBON
REFRIGERANT



LOW CARBON



FULL SCOPE
ISO 14001



LOW PRODUCT MILES

Demand more. Choose Foster