



Demand more. Choose Foster

Foster Display Chiller 1500mm Open Front Self Service FDC1500



Temperature



Refrigerator 1/4 °C

Dimensions (mm)

W 1500 D 785

H 1435



Capacity

200 Litres

Unpacked Weight

Features & Benefits

If you want best in class British made self-service display, Foster Display Chillers are for you, giving your customers every opportunity to buy on impulse without losing produce quality. The open fronted range is perfect for the storage and display of pre-packaged products such as drinks, sandwiches, sushi and dairy produce.

- ACT (Anti Condensation Technology) helps glass to remain clear, maximising product display
- Glass end panels over 70% wider than many models in the market, maximising your display window
- Thick toughened glass for enhanced safety across both open and closed fronted models
- Manufactured using superior 304 stainless steel – the 'gold standard' in performance finishes meaning quality is assured
- Foster's innovative air curtain protects your merchandise from warmer air entering the display ensuring your food keeps both its taste and texture
- Brilliantly bright LED lighting in top canopy and on every shelf significantly enhances product display
- Innovative design means the controller can be positioned to the front or rear – allowing on site flexibility
- There when you need us: Unrivalled 2 year parts and labour warranty as standard for complete peace of mind (UK only)

| External Finish | |
|---------------------------|----------------------|
| 304 Stainless Steel | Standard |
| Internal Finish | |
| 304 Stainless Steel | Standard |
| Shelving | |
| 10mm Thick Glass Shelving | Quantity: 3 Standard |
| Base Fittings | |
| Roller Castors | Standard |

| Refrigeration | |
|---------------|--|
| Forced Air | Standard |
| Integral | Standard |
| Depth | Please allow an additional 80mm to the depth of the product as spacers are required for air circulation (fitted as standard). The unit is designed to operate at M2 temperature requirements (EN441 Climate Class 3 25° ambient) |
| Note: | |
| R404a | Standard |

| Electrical Data & Service Information | |
|---------------------------------------|----------|
| 230 Volts | Standard |
| 50Hz | Standard |
| 1 Phase | Standard |
| Fuse Required (A) | 13 amp |

Footnotes

- Add 80mm to depth for spacers if product is to be wall-sited (required for air circulation - detachable if not wall-sited)

Foster Refrigerator

Oldmedow Road - King's Lynn - Norfolk - PE30 4JU - United Kingdom

Telephone: **0843 216 8800** Facsimile: **0843 216 4700** Email: sales@foster-uk.com

**FOSTER
GREEN
PROCUREMENT**



Demand more. Choose Foster